


Swing Patio Door

Configurations



Minimum/Maximum Sizes

In-Swing Door

_	1 Panel	Min 2º 66	Max $3^2 8^0$
-	1 Panel, 1 Sidelite	Min 3 ⁴ 6 ⁶	Max 5280
-	1 Panel, 2 Sidelite	Min 48 66	Max 7 ² 8 ⁰
-	2 Panel	Min 4º 66	Max 64 80
-	2 Panel, 1 Sidelite	Min 5 ⁴ 6 ⁶	Max 8 ⁴ 8 ⁰
-	2 Panel, 2 Sidelite	Min 68 66	Max 10 ⁰ 8 ⁰

Out-Swing Door

_	1 Panel	Min 2º 6°	Max 3 ² 8 ⁰
_	1 Panel, 1 Sidelite	Min 3 ⁴ 6 ⁶	Max 5 ² 8 ⁰
_	1 Panel, 2 Sidelite	Min 48 66	Max 7 ² 8 ⁰
_	2 Panel	Min 4 ⁰ 6 ⁶	Max 6 ⁴ 8 ⁰
_	2 Panel, 1 Sidelite	Min 5 ⁴ 6 ⁶	Max 8 ⁴ 8 ⁰
_	2 Panel, 2 Sidelite	Min 68 66	Max 10 ⁰ 8 ⁰

Available Frame Styles

- 1-3/8" Setback 4-9/16" Wall Condition
- 1-3/8" Setback 6-9/16" Wall Condition
- 1-3/8" Setback 4-9/16" Wall Condition

Other

All configurations available with transoms, 1 or 2 sidelites and arches.

NOTE: For engineering approval contact your Milgard representative for any configuration over 40 square feet. Each Milgard Manufacturing plant reserves the right to alter or change sizes and configurations according to location capabilities. Ask your Milgard rep about specialty applications. Windows over 40 square feet shipped open for field glazing. Varies by location.

Not all frame styles available at all Milgard locations. Contact your Milgard Representative for more information.