



Single Hung Window


SH Configurations





Single Hung

Double Single Hung



Gable Top Single Hung



Double Single Hung/Center Lite



Triple Single Hung

NOTE: For engineering approval contact your Milgard representative for any configuration over 40 square feet. Each Milgard Manufacturing plant reserves the right to alter or change sizes and configurations according to location capabilities. Ask your Milgard rep about specialty applications. Windows over 40 square feet shipped open for field glazing. Varies by location.

Not all frame styles available at all Milgard locations. Contact your Milgard Representative for more information.

SH Minimum/Maximum Sizes

SINGLE-HUNG

Min 1⁶2⁰ Max 4⁰7⁶

DOUBLE SINGLE-HUNG

- Min $3^{\circ}2^{6}$ Max $8^{\circ}7^{\circ}$

TRIPLE SINGLE-HUNG

- Min 4⁶2⁶ Max 9⁰7⁰

Minimum egress is $3^{\circ}5^{\circ}$ with a 30'' bar set or

266 with a 36 bar set.

SH vent set: 12", 15", 18", 21", 24", 27", 30", 33" or 36"

SH Available Frame Styles

NO NAIL-ON FIN:

8220T Block Frame

8270T 1-5/8" Narrow Z-Bar (Tuscany only)

8240T 2-1/8" Wide Z-Bar (Tuscany only)

INCLUDES NAIL-ON FIN:

8220T 1-3/8" Nail Fin Setback

8230T 1" Nail Fin Setback with Stucco Key

8240T 1-3/8" Nail Fin Setback, 2" Long Nail Fin

8240T 1-3/8" Nail Fin Setback, 2" Long Nail Fin with optional:

- 3/4" Flat J-channel
- 1" Contoured J-channel
- 2" Brickmold-style J-channel
- Welded Brickmold

© Milgard Manufacturing, Inc.