

Performance Ratings

Updated: 8/2014

Window Type	Series	Test		Structural Class	Air Infiltration	Water * Test (PSF)	Min					Max					
		size	bs/vs				Width		Height		bs/vs	Width		Height		bs/vs	
Half Vent	3110	6060	-	LC-PG-30	0.1	4.5	2	0	1	4	-	6	0	6	0	-	
Double Vent		12060	48	HS-LC-25	0.02	3.75	5	0	1	4	12	12	0	6	0	48	
Half Vent Below / Above		-	-	-	-	-	-	2	0	2	4	-	6	0	6	0	24
Double Vent Below / Above		-	-	-	-	-	-	5	0	2	4	-	10	0	6	0	24
Single Hung	3210	4978	C	LC-PG-30	0.1	4.5	1	6	2	0	12	4	9	7	8	45	
Double Single Hung		-	-	-	-	-	3	0	2	0	12	8	0	7	6	45	
Triple Single Hung		-	-	-	-	-	-	4	6	2	0	12	9	0	7	6	45
Double Hung	3275	net 44 x 75	38	H-LC-40	0.16	6.75	1	6	2	9	12	3	8	6	3	42	
Double Hung		4070	C	H-LC-35	0.16	-	1	6	2	9	12	4	0	7	0	42	
Double Double Hung		-	-	H-LC-40	-	-	3	6	2	9	12	8	0	7	0	42	
Triple Double Hung		-	-	H-LC-40	-	-	5	3	2	9	12	12	0	7	0	42	
Double Hung	3285	net 44 x 75	38	H-LC-40	0.16	6.75	1	6	2	9	12	3	8	6	3	42	
Double Hung		4070	C	H-LC-35	0.16	6	1	6	2	9	12	4	0	7	0	42	
Double Double Hung		-	-	H-LC-40	-	-	3	6	2	9	12	8	0	7	0	42	
Triple Double Hung		-	-	H-LC-40	-	-	5	3	2	9	12	12	0	7	0	42	
Picture Window	3310	8060	-	FW-HC-50	0.01	12	1	0	1	0	-	8	0	6	0	-	
Picture Window	3315	8060	-	FW-HC-50	0.01	12	1	0	1	0	-	8	0	6	0	-	
Octagon		-	-	FW-HC-50	-	-	2	0	2	0	-	6	0	6	0	-	
Picture Window	3371	net 72 x 72	-	FW-HC-40	0.08	6	1	0	1	0	-	6	0	6	0	-	
Picture Window	3375	6060	-	FW-C-40	0.02	6	1	0	1	0	-	6	0	6	0	-	
Picture Window	3385	6070	-	FW-LC-PG35	0.18	5.25	1	6	1	6	-	6	0	7	0	-	
Full Round		8060	-	FW-HC-40	0.01	12	2	0	2	0	-	8	0	6	0	-	

1/2 Round	3710	-	-	FW-HC-40	-		2	0	1	0	-	8	0	4	0	-	
1/4 Round		-	-	FW-HC-40	-		1	0	1	0	-	6	0	6	0	-	
Full Awning	3410	net 60 x 36	-	CW-PG35	0.01	6.75	1	7	1	6	-	5	0	3	0	-	
Double Awning		-	-	-	-			3	2	1	6	-	10	0	3	0	-
Full Casement	3510	net 32 x 78	-	DP 30	.07	6.00	1	6	2	0	-	2	8	6	6	-	
Full Casement		3050	-	C-C-45	0.1		1	6	2	0	-	3	0	5	0	-	
Fixed Casement		net 96 x 72	-	C-C-30	0.01	6		1	6	2	0	-	8	0	6	0	-
Double Casement		6050	-	C-C-45	0.1	7.5		3	0	2	0	-	6	0	5	0	-
FD 1 panel Multi Point Lock	3621	-	-	SHD-C-30	-		2	6	6	8	-	3	0	8	0	-	
FD 1 panel Single Point Lock		-	-	SHD-C-40	-		2	6	6	8	-	2	6	6	10	-	
FD 2 panel Multi Point Lock		8080	-	SHD-C-30	0.02	4.5		5	0	6	8	-	8	0	8	0	-
FD 2 panel Single Point Lock		6080	-	SHD-C-40	0.1	6		5	0	6	8	-	6	0	8	0	-
FD 3 panel Multi Point Lock		-	-	-	-			7	6	6	8	-	12	0	8	0	-
FD 3 panel Single Point Lock		-	-	-	-			7	6	6	8	-	9	0	6	10	-
SGD OX / XO	3626	8080	-	LC-PG30	0.25	4.5	5	0	6	8	-	8	0	8	0	-	
		net 120x96	-	R-PG20	0.1	3		5	0	6	8	-	10	0	8	0	-
SGD OXO		12080	-	SD-C-30	0.14	4.5		7	6	6	8	-	12	0	8	0	-
SGD OOX		12080	-	SD-C-30	0.14	4.5		7	6	6	8	-	12	0	8	0	-
SGD OXXO		12080	-	SD-R-20	0.18	3.75		10	0	6	8	-	12	0	8	0	-
FD 1 panel	3642 3662	-	-	SHD-LC-45/50	-		2	6	6	8	-	3	0	8	0	-	
FD 2 panel		6090	-	SHD - LC-25	0.15	5.25		5	0	6	8	-	6	0	9	0	-
FD 2 panel		6080	-	SHD-LC-45	0.08	7.5		5	0	6	8	-	6	0	8	0	-
FD 2 panel		net 75 x 82	-	SHD-LC-50	0.08	7.5		5	0	6	8	-	6	3	6	10	-
FD 3 panel		-	-	-	-			7	6	6	8	-	9	0	8	0	-
FD 4 panel		12080	.	SHD-LC30	0.04	6.75		10	0	6	8		12	0	8	0	.
FD 4 panel XXXX SIDE LITES		10080	.	SHD-LC30	0.1	4.5		10	0	6	8	-	10	0	8	0	-
FD 1 panel (outswing)		-	-	SHD-LC-40/45	-		2	6	6	8	-	3	0	8	0	-	
FD 2 panel (outswing)		6080	-	SHD-LC-45	0.19	7.5		5	0	6	8	-	6	0	8	0	-

FD 2 panel (outswing)	3645 3665	60610	-	SHD-LC-40	0.14	7.5	5	0	6	8	-	6	0	6	10	-
FD 3 panel (outswing)		-	-	-	-		7	6	6	8	-	9	0	8	0	-
FD 4 panel (outswing)		12080	.	SHD-LC30	0.04		10	0	6	8		12	0	8	0	.
FD 4 panel XXXX SIDE LITES		10080	.	SHD-C35	0.23	5.25	10	0	6	8	-	10	0	8	0	-
Inswing Transom (Direct Glaze)	3643 3644 3646 3647	6060	-	FW-C30	0.02	4.5	1	6	1	0	-	6	0	6	0	-
Inswing Transom (Panel Glaze)		6060	-	FW-HC40	0.01	7.5	1	6	1	6	-	6	0	6	0	-
Outswing Transom (Direct Glaze)		6060	-	TR-C50	0.01	12	1	6	1	0	-	6	0	6	0	-
Outswing Transom (Panel Glaze)		6060	-	TR-C40	0.05	6	1	6	1	6	-	6	0	6	0	-
FD 2 panel (outswing ADA)	3845	net 74 x 96	-	SHD - PG40	0.14	Limited water	5	0	6	8	-	6	2	8	0	-

* The water test pressures are done in a controlled environment and performance in the field may vary. Therefore, AAMA requirements should be reduced to 2/3's of the test pressure for field testing.