



Cable Bay Window


Configurations



Bay Picture



Bay Casement



Bay Single Hung

NOTE: For engineering approval contact your Milgard representative for any configuration over 40 square feet. Each Milgard Manufacturing plant reserves the right to alter or change sizes and configurations according to location capabilities. Ask your Milgard rep about specialty applications. Windows over 40 square feet shipped open for field glazing. Varies by location.

Not all frame styles available at all Milgard locations. Contact your Milgard Representative for more information.

Minimum/Maximum Sizes

BAY PICTURE

- Min 4'0" ⁶ Max 8'5" ⁰

BAY SINGLE-HUNG

- Min 4'0" ⁶ Max 8'5" ⁰

BAY CASEMENT

(refer to casement/awning section for maximum vent size)

- Min 4'0" ⁶ Max 8'5" ⁰

Available Frame Styles

8000 series: with single-hung flankers

8000 series: with picture window flankers

8000 series: with casement flankers

A 1-1/4" pre-punched nail flange extends around the perimeter frame, securing the window in rough openings and acting as flashing. Fin setbacks are available in 1-3/8" from outside of frame; also in 1" for our SW locations using 3 coat stucco applications (not available at all locations).

Cable

High tensile-strength steel aviation cable is used for maximum strength and longevity.

Seat Boards

Available in PVC or PVC/Oak.