

# Performance Ratings and Min/Max Sizes

Updated: 8/2014

Window Type	Series	Test		Structural Class	Air Infiltration	Water * Test (PSF)	Min			Max				
		size	bs/vs				Width	Height	bs/vs	Width	Height	bs/vs		
Horizontal Slider	9100	6050	C	LC-PG40	0.19	7.5	33	20.5	-	6	0	5	0	36
Double Vent		10050	36	R-PG20	0.24	3	49.5	20.5	-	10	0	5	0	36
Double Hung	9200	4080	C	LC-PG-45	0.11	6.75	17.5	29.5	-	4	0	8	0	C
Double Hung		3056	C	LC-PG-45	0.21	6.75	17.5	29.5	-	3	0	5	6	C
Double Hung		net 52 x 75	C	LC-PG-35	0.2	5.25	17.5	29.5	-	4	4	6	3	C
Picture Window	9300	6060	-	CW-PG50-FW	0.01	7.5	11.5	11.5	-	6	0	6	0	-
Double Hung Fixed	9310	6060	-	CW-PG-40	0.04	7.5	17.5	20.5	-	6	0	6	0	-
Double Hung Fixed		net 96 x 72	-	CW-PG-30	0.03	7.5	17.5	20.5	-	8	0	6	0	-
Awning/Casement Fixed	9340 9350	6060	-	CW-PG60-FW	0.04	9	17.5	17.5	-	6	0	6	0	-
Fixed		8060	-	CW-PG-50	0.02	9	17.5	17.5	-	8	0	6	0	-
Awning	9400	5030	-	AP-C-40	0.02	12	21.5	19.5	-	5	0	3	0	-
Awning		5050	-	R-PG-20	0.04	12	21.5	19.5	-	5	0	5	0	-
Casement	9500	net 35.5 x 60	-	CW-PG60-C	0.03	9	17.5	23.5	-	3	0	5	0	-
Casement		3070	-	CW-PG-40	0.05	12	17.5	23.5	-	3	0	7	0	-
Radius Picture Window	9700	6060	-	CW-PG50-FW	0.01	7.5	Std	Std	-	6	0	6	0	-

\* The water test pressures are done in a controlled environment and performance in the field may vary. Therefore, AAMA requirements should be reduced to 2/3's of the test pressure for field testing.