

Hermosa™ Series



Clearly. the best.™

Performance Ratings

All products are AAMA Gold labeled for thermal performance

Rev: 3/8/17

Operating Style	Series #	Test		Performance Grade	Structural Class	Air Infiltration	Water * Test (PSF)	Water * Test (PA)	AAMA Label	
		Size	bs/vs						Silver	Gold
Single Hung Tilt	10215	44 x 75	37 1/2	PG50	LC	0.18	7.5	360		x
Single Hung Tilt		48 x 84	42	PG30	LC	0.08	7.5	360		x
Single Hung Tilt		48 x 96	36	PG30	LC	0.08	7.5	360		x
Double Single Hung Tilt		72 x 84	42	PG30	LC	0.12	6	220		x
Double Single Hung Tilt		96 x 96	36	PG30	LC	0.08	7.5	360		x
Triple Single Hunt Tilt		108 x 75	37 1/2	PG40	LC	0.12	6	290		x
Triple Single Hunt Tilt		108 x 96	36	PG35	LC	0.08	6	290		x
Horizontal Slider	10120	72 x 60	36	PG30	LC	0.08	5.25	260		x
Horizontal Slider		72 x 72	36	PG30	LC	0.08	5.25	260		x
Double Vent		120 x 72	36	PG25	LC	0.01	3.75	260		x
Picture Window	10320	96 x 72	-	PG45	CW	0.01	7.5	330		x
Picture Window		144 x 48	-	PG30	LC	0.01	6	290		x
Picture Window		7060	-	PG50	CW	0.01	7.5	360		x
Full Awning	8420MH	60 x 36	-	PG40	C	0.03	12	580		x
Bottom/Top Awning		60 x 96	36	PG40	C	0.03	12			x
Full Casement	8520MH	32 x 72	-	PG50	C	0.07	12	580		x
Full Casement		35 1/2 x 60	-	PG60	C	0.08	12	580		x
Double Casement		72 x 60	36	PG40	C	0.07	6	290		x
Double Casement w/ Center PW		144 x 72	36	PG35	C	0.09	5.25	260		

* The water test pressures are done in a controlled environment and performance in the field may vary. Therefore, AAMA requirements should be reduced by 2/3's of test pressure for field testing.