

Aluminum Series

Performance Ratings

Updated: 7/2020

Window Type	Series	Test		Report Number	Structural Class	Air Infiltration	Water * Test	Min					Max					
		size	bs/vs					Width	Height	bs/vs	Width	Height	bs/vs					
Half Vent	1110H 1110SH 1180H 1280H	-	-	C8511 01-301-44	HS-R-20	-		2	0	1	0	-	6	0	6	0	-	
Double Vent		net 120 x 72	36	C8511 01-301-44	HS-R-20	0.23	3	4	0	1	0	12	10	0	6	0	36	
Half Vent Below/Above		-	-	-	-	-	-		2	0	2	0		6	0	7	0	
Double Vent Below/Above		-	-	-	-	-	-		4	0	2	0		8	0	7	0	
Single Hung	1510	4070	C	C3488 01-301-44	LC-PG25	0.12	3.75	1	6	2	6	12	4	0	7	0	42	
Double Single Hung	1510S	-	-	-	-	-		3	0	2	6	12	8	0	6	6		
Triple Single Hung	1580	-	-	-	-	-		4	6	2	6	12	12	0	6	6		
Picture Window PW2VM)	710 710S	8060	- C	NS2010-464 NS2010-465	FW-CW-40	0.01	9	1 2	0 0	1 1	0 0	- -	8 8	0 0	6 6	0 0	- -	
Picture Window	910C	8060	-	C3487 01-301-44	FW-C45	0.01	6.75	1	0	1	0	-	8	0	6	0	-	
Octagon	910S	-	-	C3487 - qualifies	FW-C45	-		2	6	2	6	-	6	0	6	0	-	
Full Round PW	R15 R15S	6060	-	B9566.01	CW-PG35	0.01	12	2	6	2	6	-	6	0	6	0	-	
1/2 Round		-	-	B9556.01 - qualifies	CW-PG35	-		2	6	1	3	-	8	0	4	0	-	
1/4 Round		-	-	B9556.01 - qualifies	CW-PG35	-		1	3	1	3	-	6	0	6	0	-	
Picture Window	1185 1185H	6060	-	J2662.01-301-44 RO	FW-LC-25	0.02	3.76	1	0	1	0	-	6	0	6	0	-	
Picture Window	1285 1285H	6060	-	C8494.01-301-44	FW-C-35	0.01	12	1	0	1	0	-	6	0	6	0	-	
Full Awning	910C	-	-	2233- qualifies	AP-C-30	-		1	6	1	6	-	4	0	3	0	-	
Double Awning	910S	-	-	-	-	-		3	0	1	6	-	8	0	3	0	-	
Bottom Awning	911C	4080	36	310-2233	AP-C-30	0.04	4.5	1	6	2	0	12	4	0	8	0	36	
Full Casement (Roto)		2660	-	C0127.01-301-44	R-PG-30	0.12	4.5	1	6	1	6	-	2	6	6	0	-	
Full Casement (Roto)		-	-	006 - qualifies	C-LC-30	-			1	6	1	6	-	2	6	5	0	-

Full Casement (Push out)	910C 910S	net 36 x 60	-	<u>310-3709</u>	LC-PG40	0.07	5.25	1	6	1	6	-	3	0	5	0	-
Single Casement (Roto)	911C	-	-	006 - qualifies	C-LC-30	-		3	0	1	6	18	8	0	5	0	32
Double Casement (Roto)		-	-	006 - qualifies	C-LC-30	-		3	0	1	6	-	5	0	5	0	-
center PW (Roto)		9050	32	S2009-006	C-LC-30	0.24	4.5	4	0	1	6	18	9	0	5	0	32
SGD OX / XO	450 450S	6088	-	310-2234	SD-R-20	0.17	3	5	0	6	8	-	6	0	8	8	-
SGD OX / XO		8080	-	N/A	SD-R-20	-	-	5	0	6	8	-	8	0	8	0	-
SGD OXO		-	-	N/A	SD-R-20	-		9	0	6	8	-	12	0	8	0	-
SGD OXXO		16080	=	N/A	SD-R-20	0.18	3	10	0	6	8	-	16	0	8	0	-

* The water test pressures are done in a controlled environment and performance in the field may vary. Therefore, AAMA requirements should be reduced to 2/3's of the test pressure for field testing.
