

# Performance Ratings



Clearly the best.™

Updated: 07/2020

Window Type	Series	Test		Report Number	Structural Class	Air Infiltrati	Water * Test	Min						Max			
		size	bs/vs					Width		Height		bs/vs	Width		Height	bs/vs	
Half Vent	6110 6130 6130J 6170	6050	-	310-2484	HS-LC-25	0.05	3.75	2	0	1	0	-	6	0	5	0	-
Double Vent		10060	30	310-2707	HS-R-15	0.1	3	4	0	1	0	12	10	0	6	0	36
Double Vent		9050	36	310-1478	HS-LC-25	0.1	3.75	4	0	1	0	12	9	0	5	0	36
Half Vent Below / Above		-	-	2157/2158 - qualifies	HS-R-20	-		2	0	2	0		6	0	6	0	
Double Vent Above		8060	48 / 24	310-2158	HS-R-20	0.08	3	4	0	2	0		8	0	6	0	48 / 24
Double Vent Below		8060	48 / 24	310-2157	HS-R-20	0.08	3	4	0	2	0		8	0	6	0	48 / 24
Single Hung	6210 6230 6230J 6270	net 48 x 78	C	310-1477	H-LC-30	0.06	4.5	1	0	2	6	12	4	0	6	6	
Single Hung		net 44 x 75	C	310-2527	H-LC-30	0.1	4.5	1	0	2	6	12	3	8	6	3	
Single Hung		4080	C	K2414.01-901-47	H-LC-25	0.1	3.76	1	0	2	6	-	4	0	8	0	
Single Hung		4080	42	K2412.01-901-47	H-R-20	0.1	3.76	1	0	2	6	-	4	0	8	0	
Triple Single Hung		net 108 x 75	C	310-3437	H-R-20	0.11	3	3	0	2	6	12	9	0	6	3	
Picture Window	6310	6060	-	310-1164	FW-CW-40	0.04	6	1	0	1	0	-	6	0	6	0	-
Picture Window	6340	8060	-	NS2010-126	FW-CW-40	0.01	12	1	0	1	0	-	8	0	6	0	-
Picture Window	6350 6360 6360J	6060	-	310-2359	FW-CW-35	0.01	12	1	0	1	0	-	6	0	6	0	-
Awning	6410	net 48 x 36	-	310-2350	AP-LC-45	0.01	9	-	-	-	-	-	4	0	3	0	-
Full Awning stacked 2 vertically	6430 6430J	4060	-	310-2360	AP-LC-40	0.03	9	-	-	-	-	-	4	0	6	0	-
Double Awning Below		net 84x84	36	J9329.01-901-47	AP-R-20	0.30	3	4	0	4	0		7	0	7	0	36
Full Casement	6510 6530 6530J 6570	net 36 x 60	-	310-2351	C-LC-40	0.05	7.5	-	-	-	-	-	3	0	5	0	-
Full Casement		net 36x72	-	J3630.01-907-47	C-LC-30	0.20	4.5	1	0	2	0	-	3	0	6	0	-
Single Casement		6060	36	310-2479	C-LC-30	0.01	9	-	-	-	-	-	6	0	6	0	36
Double Casement		net 72 x 72		J3554.01-901-47	C-R-20	0.20	4	3	0	1	0		6	0	6	0	36
Double Casement w/ center PW		net 143 x 60	36	310-2482	C-LC-25	0.08	7.5	-	-	-	-	-	11	11	5	0	36

SGD OX / XO	6610 6630	8080	-	C0154 01-901-44	SD-R-15	0.12	4.5	5	0	6	8	-	8	0	8	0	-
SGD OX / XO		80610	-	C0152 01-901-44	SD-R-20	0.06	4.5	5	0	6	8	-	8	0	6	10	-
SGD O/OX / O/XO		6090	26	S2007-360	SD-LC-35	0.02	5.25	6	0	6	8	-	6	0	9	0	26
Picture (Transom) Window	6610TR 6630TR	8060	-	310-2703	TR-CW-35	0.01	5.25	1	6	1	6	-	8	0	6	0	-

\* The water test pressures are done in a controlled environment and performance in the field may vary. Therefore, AAMA requirements should be reduced to 2/3's of the test pressure for field testing.

---