

Operating Style	Series	Min				Max				Maximum Sq. Ft.	Minimum Radius	
		Width		Height		Width		Height				
Horizontal Slider	3110	2-0	23.5"	1-4	15.5"	-	6-0	71.5"	6-0	71.5"	-	-
Double Vent		5-0	59.5"	1-4	15.5"	12"	12-0	143.5"	6-0	71.5"	48"	-
Half Vent Below/Above		2-0	23.5"	2-4	27.5"	-	6-0	71.5"	6-0	71.5"	24"	-
Double Vent Below/Above		5-0	59.5"	2-4	27.5"	-	10-0	119.5"	6-0	71.5"	24"	-
Single Hung	3210	1-6	17.5"	2-0	23.5"	12"	4-9	56.5"	7-8	91.5"	45"	-
Double Single Hung		3-0	35.5"	2-0	23.5"	12"	8-0	95.5"	7-6	89.5"	45"	-
Triple Single Hung		4-6	53.5"	2-0	23.5"	12"	9-0	107.5"	7-6	89.5"	45"	-
Picture Window	3310	1-0	11.5"	1-0	11.5"	-	8-0	95.5"	6-0	71.5"	-	-
Picture Window	3315	1-0	11.5"	1-0	11.5"	-	8-0	95.5"	6-0	71.5"	-	-
Octagon		2-0	23.5"	2-0	23.5"	-	6-0	71.5"	6-0	71.5"	-	-
Picture Window	3371	1-0	11.5"	1-0	11.5"	-	6-0	71.5"	6-0	71.5"	-	-
Picture Window	3375	1-0	11.5"	1-0	11.5"	-	6-0	71.5"	6-0	71.5"	-	-
Picture Window	3385	1-6	29.5"	1-6	29.5"	-	6-0	71.5"	7-0	83.5"	-	-
Full Round	3710	2-0	23.5"	2-0	23.5"	-	8-0	95.5"	6-0	71.5"	-	-
Half Round		2-0	23.5"	1-0	11.5"	-	8-0	95.5"	4-0	47.5"	-	-
Quarter Round		1-0	11.5"	1-0	11.5"	-	6-0	71.5"	6-0	71.5"	-	-
Awning	3410	1-7	18.5"	1-6	17.5"	-	5-0	59.5"	3-0	35.5"	-	-
Double Awning		3-2	37.5"	1-6	17.5"	-	10-0	119.5"	3-0	35.5"	-	-
Full Casement	3510	1-6	17.5"	2-0	23.5"	-	3-0	35.5"	5-0	59.5"	-	-
Fixed Casement		1-6	17.5"	2-0	23.5"	-	8-0	95.5"	6-0	71.5"	-	-
Double Casement		3-0	35.5"	2-0	23.5"	-	6-0	71.5"	5-0	59.5"	-	-
FD 1 Panel Multipoint Lock	3621	2-6	29.5"	6-8	79.5"	-	3-0	35.5"	8-0	95.5"	-	-
FD 1 Panel Single Point Lock		2-6	29.5"	6-8	79.5"	-	2-6	29.5"	6-10	81.5"	-	-
FD 2 Panel Multipoint Lock		5-0	59.5"	6-8	79.5"	-	8-0	95.5"	8-0	95.5"	-	-
FD 2 Panel Single Point Lock		5-0	59.5"	6-8	79.5"	-	6-0	71.5"	8-0	95.5"	-	-
FD 3 Panel Multipoint Lock		7-6	89.5"	6-8	79.5"	-	12-0	143.5"	8-0	95.5"	-	-
FD 3 Panel Single Point Lock		7-6	89.5"	6-8	79.5"	-	9-0	107.5"	6-10	81.5"	-	-
SGD OX/XO	3626	5-0	59.5"	6-8	79.5"	-	10-0	119.5"	8-0	95.5"	-	-
SGD OXO		7-6	89.5"	6-8	79.5"	-	12-0	143.5"	8-0	95.5"	-	-
SGD OOX		7-6	89.5"	6-8	79.5"	-	12-0	143.5"	8-0	95.5"	-	-
SGD OXXO		10-0	119.5"	6-8	79.5"	-	12-0	143.5"	8-0	95.5"	-	-
FD 1 Panel (inswing)	3642 3662	2-6	29.5"	6-8	79.5"	-	3-0	35.5"	8-0	95.5"	-	-
FD 2 Panel (inswing)		5-0	59.5"	6-8	79.5"	-	6-0	71.5"	9-0	107.5"	-	-
FD 3 Panel (inswing)		7-6	89.5"	6-8	79.5"	-	9-0	107.5"	8-0	95.5"	-	-
FD 4 Panel (inswing)		10-0	119.5"	6-8	79.5"	-	12-0	143.5"	8-0	95.5"	-	-
FD 4 Panel w/ Sidelites (inswing)		10-0	119.5"	6-8	79.5"	-	10-0	119.5"	8-0	95.5"	-	-
FD 1 Panel (outswing)	3645 3665	2-6	29.5"	6-8	79.5"	-	3-0	35.5"	8-0	95.5"	-	-
FD 2 Panel (outswing)		5-0	59.5"	6-8	79.5"	-	6-0	71.5"	8-0	95.5"	-	-
FD 3 Panel (outswing)		7-6	89.5"	6-8	79.5"	-	9-0	107.5"	8-0	95.5"	-	-
FD 4 Panel (outswing)		10-0	119.5"	6-8	79.5"	-	12-0	143.5"	8-0	95.5"	-	-
FD 4 Panel w/ Sidelites (outswing)		10-0	119.5"	6-8	79.5"	-	10-0	119.5"	8-0	95.5"	-	-

Minimum/Maximum Sizes

Operating Style	Series	Min				Max				Maximum Sq. Ft.	Minimum Radius	
		Width	Height	bs/vs	Width	Height	bs/vs					
Inswing Transom (direct glaze)	3643	1-6	17.5"	1-0	11.5"	-	6-0	71.5"	6-0	71.5"	-	-
Inswing Transom (panel glaze)	3644	1-6	17.5"	1-6	17.5"	-	6-0	71.5"	6-0	71.5"	-	-
Outswing Transom (direct glaze)	3646	1-6	17.5"	1-0	11.5"	-	6-0	71.5"	6-0	71.5"	-	-
Outswing Transom (panel glaze)	3647	1-6	17.5"	1-6	17.5"	-	6-0	71.5"	6-0	71.5"	-	-
FD 2 Panel ADA (outswing)	3845	5-0	59.5"	6-8	79.5"	-	6-2	73.5"	8-0	95.5"	-	-